

# TECHNICAL DATA SHEET



## PRODUCT SPECIFICATION

**Treasure Lakes**  
STONE POLYMER COMPOSITE

**Sky Painted**

**Mercury**  
HERRINGBONE

Collection			Treasure Lakes	Sky Painted	Mercury
Format			Plank	XL Plank	Herringbone
Floor type			Click SPC vinyl flooring		
Overall thickness		ISO 24337	7 mm		
Wear layer		EN 429	0,5 mm	0,75 mm	0,75 mm
Plank size		ISO 24337	1520 x 230 mm	1830 x 235 mm	635 x 127 mm
Total weight		ISO 23997	10500 kg/m2		
Construction			virgin base material		
Composition			Polyvinyl chloride 30 - 35 % , Calcium Carbonate 60 - 65 % , Stabilizer 3.5 - 4.8 % , Lubricant 1 - 1.2 %		
Surface			embossed-in-register (EIR)		
Groove			4 sides painted groove		
Top layer			UV coating, Anti-bacterial, Anti-dusty		
Installation			Click		
Warranty			lifetime for residential, 10 years commercial, 5 years light industrial		
Pieces per box			6	5	10 (A and B)
Area per box			2.0976 m2	2.1511 m2	0.986 m2
Weight per box			23 kg	22 kg	10 kg
Fire resistance		EN 13501-1	Bfl-s1		
Formaldehyde emission		EN 14041	E1		
Slip resistance		EN 13893	DS		
Dimension stability		EN 23999	norm: $\leq 0.25\%$ $\leq 0.15\%$		
Dimension stability		EN 23999	pass ( $\leq 2$ mm)		
Wear group classification		EN ISO 10874	23: domestic heavy 33: commercial heavy 42: light industrial general		
Abrasion resistance		EN 660-2	group T		
Castor chair		EN 425	pass (no visible change)		
Residual indentation		EN 434	pass ( $\leq 0,1$ mm)		
Stain resistance		EN 438	pass (grade 5)		
UV resistance		ISO 105-B02	pass ( $\geq 6$ )		
Thermal conductivity		EN 12524	0,25 W/mK		
Thermal resistance		EN 12524	0,012 (m2K)/W		
Underfloor heating			suitable for underfloor heating under certain conditions		
Acoustic insulation		EN ISO 717-2	$\Delta L_w$ 3 dB		



FLOOR OF YOUR DREAM

**CityPlus sp. z o.o.**

ul. Prezydenta Gabriela Narutowicza 40/1, 90-135 Łódź  
NIP: 7252339345  
REGON: 527417404  
KRS: 0001080459

www.cityplus.com.pl

